



E5® Protect enhances the beauty of polished and dyed concrete and provides lasting protection to interior and exterior concrete.

E5® Protect is an environmentally friendly sealant that deeply penetrates into the concrete surface. This nano acrylic sealant creates a dust-proof surface that is harder, denser and exceptionally resistant to the damaging effects of water and salt.

Specially engineered to enhance the natural beauty of polished, dyed & exterior concrete, **E5® Protect** provides lasting protection to finished surfaces. A clear, odorless solution, **E5® Protect** does not require rinsing and removal, saving considerable time and money while eliminating hazardous waste disposal issues – significantly reducing your company's impact on the environment.

E5® Protect can be used to seal interior and exterior concrete. The durable, non-yellowing low gloss finish offers superior resistance to rain, UV rays, cold and hot climates, stains and more. When applied to dull or faded surfaces it will help to enhance the natural characteristics. It can be applied to unsealed surfaces or to surfaces previously sealed with a solvent based acrylic sealer.

For interior applications, a high luster can be achieved by lightly burnishing the surface of the concrete.

Features & Benefits

- Breathable, non-yellowing, UV-resistant
- Resistant to hot tire pickup, stains, de-icing salts and some chemicals
- Self-priming, easy recoat and low maintenance
- Professional-grade, long-lasting
- Will reduce damage and deterioration caused by surface abrasion and/or water absorption"

Compatibility

E5® Protect is highly effective on its own or in combination with other E5® admixtures. If using multiple admixtures, it is critical to add each one individually to the concrete mix to ensure fullest efficacy and to provide desired results.

Application

For exterior applications, apply **E5® Protect** at 300 - 400 sq. ft. per gallon. Spray apply to concrete surface, holding tip 6 - 24 inches (15-60 cm) above the surface and moving side to side to achieve even distribution. Apply additional product as needed.

For interior applications, apply **E5® Protect** at 1,500 - 2,000 sq. ft. per gallon. Spread evenly with a microfiber pad and let dry. Once the surface has dried, finish **E5® Protect** by burnishing the surface with a diamond impregnated pad to the desired sheen.

Coverage

Exterior: 300-400 sf/gal
Interior: 1,500-2,000 sf/gal

For more information about the use of this product, please contact your local E5® Representative or the Technical Services Department at 1-888-881-1726.

Environmental Benefits

Zero VOC formula
Non-hazardous
Bio-degradable

Packaging

Size	Gallons	Liters
Pail	5	19
Drum	55	209
Tote	275	1041

Storage Instructions

Do not break seal until product is ready for use. Maintain unused product in the original container. Store in a well-ventilated, cool and dry location at temperatures between 40°-130°F (4° - 54°C). This product has a shelf life of 18 months in its original unopened container. It is **EXTREMELY important to protect from freezing, direct sunlight, and UV exposure.**



E5® Incorporated



sales@E5NanoSilica.com | 1-888-881-1726

www.E5NanoSilica.com